WABASH



The ultimate in performance, the Wabash Aluminum Drop Deck Flatbed provides exceptional fuel economy, corrosion resistance and increased capacity. Known for its fleet-proven design, this trailer offers greater load and operating flexibility, lower maintenance and longer trailer life.

Superior Main Beam. Lower Maintenance.

The two-piece, welded main beam design eliminates the need for mechanical fasteners by welding on the neutral axis of the main beam where bending stress is minimal. Unlike bolted designs, this main beam has no fasteners that eventually loosen and lead to additional maintenance.

Less Weight. More Freight.

Floor crossmembers weld to the main beam, side rail, and floor to form a super stiff structure, eliminating the need for knee braces for a lighter weight trailer and less maintenance.

Greater Flexibility. More Loaded Miles.

The Lock-Rite® multi-position tie down system offers flexibility to either tie down narrow loads to the center of the trailer or to the outside siderails. This patent-pending design also allows the use of either straps or chains to secure loads.

Better Highway Visibility.

The enhanced visibility lighting system offers three stop/tail/turn lights and five dual-function side marker lights. The side marker lights also function as turn signals for improved motorist visibility.

Specifications

General	Length: 28'-53'Width: 96" and 102"Upper Deck: 10' or 11'
Beam Rating	• 524: 52,000 in 4' / 55,000 lb in 10' / 105,000 lb evenly distributed
48' Base Weight	• 524: 9,203 lb/4,174 kg
Main Beam Design	Welded, 2-piece, 6061 T6 extruded aluminum "T" cross sections Beams welded along neutral axis Floor sections welded to top flange of main beam Top tee extrusion with integral Lock-Rite groove Main beam camber cut in lower aluminum "T" section
Front End Design	High tensile steel neck for increased strength Bright finish, fabricated aluminum front crossmember Center mount glad hands and 7-way on removable access panel 1/4" steel coupler plate welded to neck Heavy-duty cross and aft bracing
Rear End Design	Closed section extruded rear light box Three rear stake pockets with extruded pocket protector Tubular bumper uprights with flanges for mounting accessories Extruded grip surface on top of bumper tube Rubber dock bumpers mounted vertically with three bolts Bumper assemblies are United States Department of Transportation (DOT) and Transport Canada compliant
Siderail Design	Extruded box section side rail with integral Lock-Rite groove Radius edges to prevent strap damage "LL" sliding winch track roadside, bolt-on design Tumbled aluminum stake pockets on 24" centers Large diameter double pipe spools Extruded aluminum rub rail with recessed groove
Crossmember Design and Floor System	4-7/8" aluminum C-channel crossmembers on 16" centers 1-1/4" hollow core box design, extruded aluminum floor boards with four apitong nailers, two singles outside, double in the center Crossmembers welded vertically to siderail and main beam; horizontally to floor
Undercarriage	Lightweight, formed suspension crossmembers at suspension hangers and air springs Bolt-on, lower steel C-channel and strut bracing Air suspension with manufacturer's 5-year warranty 121" tandem widespread axle setting, large bearings, parallel "P" spindle wheel ends and axle alignment
Electrical Wiring / Lights	Air and electrical accessible through removable front plate Below deck air and wire routing Enhanced visibility lighting system with recessed oval lights LED lights, five side marker lights per side, dual function lights correspond with turn signals Anti-lock brake system (ABS)

Popular Options

- · Additional air and electric configurations
- · Additional aluminum components
- Alternate crossmember spacing
- Corrosion prevention packages
- · Customized bumper filler plates
- Disc brakes
- · Factory installed bulkheads
- · Specialized floor packages
- Multiple accessories, freight securement and storage options
- Multiple axle configurations, sliding suspensions and lift axles
- · Premium rear features

